
Produced in Denmark since 1901



-5°C -25°C





Gastro F3 Freezer counter

Item number: 940320220

Gastro F3 is an energy efficient, durable, and reliable freezer counter build for demanding professional use with high demands for temperature stability.

WORK ENVIRONMENT, CLEANING AND EFFICIENT USE

The counter is as standard equipped with 1 left-hand door and 2 righthand doors and ergonomic door handles. It is constructed with rounded corners. The doors have removable sealing strips for easy and efficient cleaning. The counter is delivered as standard with stainless wire shelves. It can be configured with drawers – 1/2 or 1/3 as needed.

SUSTAINABILITY

Besides being energy efficient and thus having low operational costs, the counter is produced locally in Denmark with focus on minimizing the impact of the environment, social responsibility and with energy from renewable energy sources.

SECURITY

The counter comes with up to 5 years warranty, and it has a ventilated cooling system, which ensures good temperature stability and air distribution, and that the temperature is quickly restored after door

WHAT IS G+?

G+ is Gram Professional ApS's brand for professional refrigeration and freezer products for food storage.

'G' symbolizes that we have roots in the Danish Gram Group.

'+' symbolizes that innovation is a part of our DNA and that we continuously develop, so that we always live up to the customers' needs and expectations.



TECHNICAL SPECIFICATIONS

Product name	F3 G FT DL DR DR L2 E	Energy efficiency class / EEI	D / 53,1
Product type	Professional freezer counter 1/1 GN	Energy consumption (kWh/year)	2158 kWh
Temperature range	-25/-5°C	Sound level	46,8 dB(A)
Volume (gross / net)	506 / 288 L	Warranty	Up to 5 years
Dimensions (WxDxH)	1726x700x885/950 mm	Climate class	4 (30°C/55% RH)
Material (exterior / interior)	Stainless steel / Stainless steel	Door type	Isolated doors
Weight, net	158 kg	Legs	H = 135/200 mm
Refrigerant / charge	R290 / 0,059 kg	Number of shelves (max. number)	2 per compartment / (30) – GN-measure 325x530 mm (WxD)
GWP and Co2 equivalent	3 / 0,000177 t	Equipped with	1 left-hand door and 2 right-hand doors, 6 stainless wire shelves.
Refrigeration capacity at -25°C	553 W	Variation options	Additional wire shelves (stainless), castors instead of legs, worktop with 50 mm raised rear upstand.
Connection	230 V, 50 Hz / 1,76A		
Connection load	391 W		