


BANQUET LINE (GN 2/1)
Combo - Cooling Compressor - Heating Fan

- ✓ **Combine Two Boxes in One**
- ✓ **Superb Insulation Values**
- ✓ **Outstanding Manouverability**

ScanBox Banquet Line - Combo - Compressor Cooling - Heating - Fan is a range of products suited perfectly for any commercial kitchen operation requiring hot and cold holding or transport capacity. Designed with two fully separated box compartments stacked on each other. Intuitive controls, ergonomic design and a wide range of different sizes and accessories will guarantee a perfect match with your operation. Designed with ScanBox latest Environmental Performance (ExP) technology combining increased performance with a decreased environmental impact. Designed to fit equally well back of house as well as front of house allowing exterior branding options.


Function

Two boxes in a stacked combination. One compressor cooled box and one fan heated system providing an exact and even heat distribution.. Adjustable temperature setting and moisture ventilation gets you in control of food quality. Heat up time approximately 25 minutes. Compressor cooling provides a powerful and quiet operation.

Standard Equipment
Options

Backmounted Heating	International Plugs
Rearmounted Compressor	
S/S Heater	
Adjustable Temperature	
Adjustable Moisture Vent	
European Plug Type	

Capacity

Equipped with detachable stainless steel racks allowing the air to circulate freely inside the cavity. The u-shaped guides has a tilt-stop function securing the foodcontainer and lid during loading, unloading and transport. Variety of sizes and rack configurations allowing optimal usage of the box.

Standard Equipment
Options

GN 2/1 80 mm distance	Optional level distance
Detachable Racks	
Tilt-Stop Function	

Mobility

Lightweight, yet heavy duty. A solid design made for all types transports including truck. Equipped with non-marking, high quality double bearing castors for easy manouverability even in cramped spaces. Precision moulded PPE insulation assures food temperature and safety when the box is not plugged into power.

Standard Equipment
Options

Ø160 mm Castors	Optional Sized Castors
Double Bearing Castors	Stainless Steel Castors
Transport Handles	Tow Bars

Ease of Use

Equipped with an intuitive and easy to use display conveniently positioned in front top of unit. All-around top frame allows easy handling facing the unit from any direction. The 4,5 meter long single phase spiral cord is positioned on the back of the unit.

Standard Equipment
Options

Excenter lock	Peek window
Extra Long Spiral Cord	One Grip Handle
Digital Controller in Front	
Central brake system	

Construction

A heavy duty yet lightweight construction based on a stainless steel framing, reinforced plastic exterior panels, solid high precision moulded polyurethane foam insulation and anonized aluminium interior. A smooth, hygienic and fully sealed inner cavity without welds or rivets. The frame, top hood and handles are in robust stainless steel.

Standard Equipment
Options

Smooth Hygienic Cavity
Smooth S/S Top
S/S Framing

Exterior Design

Robust and elegant Scandinavian design made for both back of house as well as front of house operations. Possibility to choose different colours as well as adapting parts or the full box according to corporate branding. Use the design and let the box be a part of the full F&B experience.

Standard Equipment
Options

Black Glossy Finish	Optional colors
Black (RAL 9005)	Signature concept

Product Safety

High quality product Made in Sweden with high level of engineering details to performance, safety and easy of use. Thorough quality and safety testing through external third party. CE marked with complimentary EMC, RoHS, REACH and electrical safety testing.





Technical Specification

Model Serie



BANQUET LINE - Combo - Cooling Compressor - Heating Fan

Product Models

CC06 + HF06

Article Number

ELCCF66

Active Cooling & Heating

Controller	Digital adjustable
Heat Source	Electric Element
Cooling Source	Compressor
Heating - Temperature Range	Between +20°C - +3°C
Cooling - Temperature Range	Ambient up to 90°C
Cooling - Refrigerant	R134a
Cooling - Charge	110
Cooling - Climate Class *4	4
Heating Time *1	21 min
Cooling time *1	30 min
Heating - Energy consumption to operating temp *2	0,28 kWh
Cooling - Energy consumption to operating temp *2	0,06 kWh

Capacity

Standard	GN 2/1
Pitch between levels	80 mm
Number of 65 mm containers	6 + 6
Number of 100 mm containers	4 + 4
Number of 150 mm containers	3 + 3
Maximum load per rack	18 kg
Maximum load in unit	216 kg
Max total weight (full unit)	325 kg


Physical Attributes

External dimensions (W x H x D) mm	740 x 1597 x 990
Internal dimensions (W x H x D) mm	536 x 573x 685
Volume	230 + 230 Liter
Net weight (empty unit)	108 kg
Door opening	270°
Lenght of Powercable	4,5m

Electrical Attributes

Rated Voltage	220-240V / 1 phase
Rated Frequency	50-60 Hz
Rated Current	4,81 A Total
Power rating	830 / 135 W
IP Code *3	22

Dimension drawings



*1 - Time for a hot unit to reach 80 ° C and for a cold unit to reach 5 ° C average temperature in the air in the cavity with 22 ° C ambient temperature.

*2 - Operating temperature in hot unit of 80 ° C and in cold unit of 5 ° C with 22 ° C ambient temperature.

*3 - IP22 = Protection against penetration of solid objects larger than 12,5 mm and protected against falling drops of water (IEC 60529)

*4 - Climate class 4 means that the unit is designed for use in ambient temperatures of up to 30 ° C.